

IAP5 Rec'd PCT/PTO 25 AUG 2006

A WINDSCREEN WIPER DEVICE

The present invention relates to a windscreen wiper device
5 comprising an elastic, elongated carrier element, as well as
an elongated wiper blade of a flexible material, which can be
placed in abutment with a windscreen to be wiped, which wiper
blade includes opposing longitudinal grooves on its
longitudinal sides, in which grooves spaced-apart
10 longitudinal strips of the carrier element are disposed,
wherein neighbouring ends of said longitudinal strips are
interconnected by a respective connecting piece, which
windscreen wiper device comprises a connecting device for an
oscillating arm, wherein said oscillating arm is pivotally
15 connected to said connecting device about a pivot axis near
one end, with the interposition of a joint part.

Such a windscreen wiper device is known from German patent
publication no. 101 30 903 (Robert Bosch GmbH). This prior
20 art windscreen wiper device is designed as a "yokeless" wiper
device, wherein no use is made of several yokes pivotally
connected to each other, but wherein the wiper blade is
biased by the carrier element, as a result of which it
exhibits a specific curvature. This known device has a first
25 coupling half fixed to the oscillating arm, as well as a
second coupling half fixed to the wiper blade, wherein two
parallel interspaced supporting walls of the second coupling
half are oriented in the longitudinal direction of the wiper
blade. Each end of a pivot pin for a joint part, which is
30 mounted on the pivot pin in a manner that permits it to swing
between the supporting walls and which is provided for
connecting the oscillating arm, is held in these supporting
walls. In order to obtain protection against environmental
influences such as snow, ice and dust, the oscillating arm is

u-shaped in the area of its coupling half, whereby the U-base covers the supporting (protective) walls and both U-limbs cover the outer sides of these supporting walls.

- 5 A disadvantage of the windscreen wiper device known from the above-mentioned German patent document is that, due to high forces exerted in practice on the connection between the connecting device and the oscillating arm, the reliability of said connection appears to diminish with the passage of time,
10 resulting in play between the connecting device and the oscillating arm. Such a play in practice has proven to lead to frictional contact between these parts and therefore to wear. A further disadvantage thereof is that many constructional parts are involved in the connection between
15 the connecting device and the oscillating arm, making the known windscreen wiper device laborious to manufacture and therefore relatively costly.

- The object of the invention is to overcome these drawbacks of
20 the prior art as indicated above, in particular to provide a windscreen wiper device wherein the connecting device and the oscillating arm are interconnected in a simple though durable and solid manner.

- 25 In order to accomplish that objective, a windscreen wiper device of the type referred to in the introduction is characterized according to the invention in that the windscreen wiper device is provided with first and second retaining means for retaining said connecting device onto
30 said oscillating arm, said first retaining means comprising at least one resilient tongue provided on said joint part engaging in a correspondingly shaped hole provided in said oscillating arm, said second retaining means comprising at

least one first stop surface provided on the oscillating arm and at least one second stop surface provided on the joint part or the connecting device, both first and second stop surfaces being spaced apart during normal operation of the
5 windscreen wiper device, wherein in case of disfunctioning of said first retaining means said connecting device is allowed to move with respect to said oscillating arm causing the second stop surface to correspondingly move towards the first stop surface until the first and second stop surfaces are
10 adjacent one another. In other words, in rest position the stop surfaces of the second retaining means are spaced apart, whereas in working position they are adjacent to each other.

Preferably, the oscillating arm has an at least substantially
15 U-shaped cross-section at the location of its connection to said joint part, wherein said hole is provided in a base of said U-shaped cross-section. Instead or in addition thereto, said joint part preferably comprises at least two lateral resilient tongues extending outwardly, wherein the
20 oscillating arm has an at least substantially U-shaped cross-section at the location of its connection to said joint part, and wherein each tongue engages in a correspondingly shaped hole provided in a leg of said U-shaped cross-section. While mounting the oscillating arm onto the connecting device/joint
25 part, the resilient tongue(s) is/are initially pushed in against a spring force and then allowed to spring back into said hole(s), thus snapping, that is clipping the resilient tongue(s) into the hole(s). In case these first retaining means would fail in actual practice, for example when the
30 resilient tongue(s) are not properly snapped into the hole(s), the second retaining means serve to hold the connecting device onto the oscillating arm after all and thus to avoid any undesired separation thereof, with all negative

consequences involved, such as lost of the wiper blade. In the event that the first retaining means would break down, the wiper blade and the connecting device attached thereto may move relative to the oscillating arm. As will be

5 explained more in detail below, such a movement takes place in longitudinal direction of the wiper blade, causing the second stop surface (provided on the joint part or the connecting device) to move towards the first stop surface (provided on the oscillating arm) in a similar way. However,

10 said relative movement of the wiper blade and the oscillating arm and thus said relative movement of both stop surfaces are blocked when the second stop surface reaches the first stop surface and is stopped by the first stop surface.

15 In one preferred embodiment of a windscreen wiper device in accordance with the invention said hole(s) has/have a closed circumference. Such (a) closed hole(s) enhance(s) the retention of the oscillating arm onto the connecting device/joint part in all directions, particularly both

20 horizontally and vertically.

In another preferred embodiment of a windscreen wiper device according to the invention the oscillating arm has an at least substantially U-shaped cross-section at the location of

25 its connection to said joint part, and wherein each leg comprises clamping members which engage round longitudinal sides of said joint part that face away from each other. These clamping members being preferably formed as inwardly bended edges integral with the legs of the U-shaped cross-

30 section, serve to further enhance the retention of the oscillating arm onto the connecting device/joint part in vertical direction, that is perpendicular to the longitudinal direction of the oscillating arm.

In another preferred embodiment of a windscreen wiper device in accordance with the invention the second stop surface is caused to correspondingly move towards the first stop surface in longitudinal direction of the wiper blade. Again, such a longitudinal relative movement of both stop surfaces will be eventually blocked when said movement of the second stop surface is stopped by the first stop surface, resulting in a retaintion in longitudinal (horizontal) direction as well.

- 10 In another preferred embodiment of a windscreen wiper device according to the invention the oscillating arm has an at least substantially U-shaped cross-section at the location of its connection to said joint part, wherein said first stop surface is provided on a leg of said U-shaped cross-section.
- 15 The first stop surface is particularly formed by a hook-shaped protrusion extending downwardly.

In another preferred embodiment of a windscreen wiper device in accordance with the invention said joint part has an at least substantially U-shaped cross-section at the location of its attachment to said connecting device, wherein said second stop surface is provided on a leg of said U-shaped cross-section. Preferably, the second stop surface is formed by a hook-shaped protrusion extending upwardly.

25

In another preferred embodiment of a windscreen wiper device according to the invention the first stop surface is formed by a transverse pin extending inwardly. In particular, the second stop surface is formed by a guiding groove in the connecting device. The guiding groove guides the transverse pin in or out the "locked" position of the oscillating arm onto the connecting device.

30

In another preferred embodiment of a windscreen wiper device in accordance with the invention said connecting device is positioned at least substantially within said joint part. Particularly, this enables to attach said joint part to said
5 connecting device by protrusions of said connecting device at the location of said pivot axis, said protrusions pivotally engaging in recesses provided in said joint part. These protrusions that function as bearing surfaces are spaced far apart, so that the forces exerted on the bearing surfaces
10 will be relatively low. As these protrusions replace the pivot pin as used in the known windscreen wiper device discussed above, less constructional components are used in connecting the connection device and the oscillating arm together. Of course, in the alternative the joint part is
15 equipped with protrusions at the location of said pivot axis, said protrusions of the joint part pivotally engaging in recesses provided in the connecting device.

In another preferred embodiment of a windscreen wiper device
20 according to the invention said joint part has an at least substantially U-shaped cross-section at the location of its attachment to said connecting device, wherein said joint part in each leg of said U-shaped cross-section is provided with a recess provided coaxially with said pivot axis. Preferably,
25 the protrusions extend outwards on either side of said connecting device (that is, outwardly in lateral direction with respect to the oscillating arm), wherein the protrusions are at least substantially cylindrical. Particularly, the recesses are correspondingly shaped.

30

In another preferred embodiment of a windscreen wiper device in accordance with the invention said joint part is made of

plastic, which includes any synthetic material having some flexibility.

In another preferred embodiment of a windscreen wiper device
5 according to the invention the oscillating arm, the
connecting device and the joint part are each made in one
piece.

The invention will now be explained in more detail with
10 reference to figures illustrated in a drawing, wherein:

- Figure 1 is a perspective, schematic view of a
windscreen device of the "yokeless" type in accordance
with the invention;
15
- Figures 2 and 3 show details of the windscreen wiper
device of figure 1, wherein various successive steps are
shown for fitting an oscillating wiper arm to a
connecting device using two different types of joint
20 parts ("spacers"), particularly illustrating the first
retaining means;
- Figure 4 is a perspective and schematic view of an end of
an oscillating wiper arm used in figure 3;
25
- Figures 5 and 6 show details of the windscreen wiper
device of figure 1, particularly illustrating a first
embodiment of the second retaining means;
- 30 - Figure 7 is a perspective and schematic view of a
connecting device and an end of an oscillating wiper arm,
particularly illustrating a second embodiment of the
second retaining means; and

- Figure 8 shows several steps in (dis)mounting the connecting device and the oscillating wiper arm of figure 7.

5 Figure 1 shows a windscreen wiper device 1 of the "yokeless" type according to the invention. Said windscreen wiper device is built up of an elastomeric wiper blade 2, in the longitudinal sides of which opposing longitudinal grooves 3 are formed, and of longitudinal strips 4 made of spring band
10 steel, which are fitted in said longitudinal grooves 3. Said strips 4 form a flexible carrier element for the rubber wiper blade 2, as it were, which is thus biased in a curved position (the curvature in operative position being that of a windscreen to be wiped). Neighbouring ends of strips 4 are
15 interconnected on either side of the windscreen wiper device 1 by means of connecting pieces 6 functioning as clamping members. In this embodiment, the connecting pieces 6 are separate constructional elements, which may be form-locked ("positive locking" or "having positive fit") as well as
20 force-locked to the ends of strips 4. In another preferred variant, said connecting pieces 6 are in one piece with the strips 4 made of spring band steel. In the latter case said connecting pieces form transverse bridges for the strips 4, as it were.

25

The windscreen wiper device 1 is furthermore built up of a connecting device 7 of plastic material for an oscillating wiper arm 8. Connecting device 7 comprises clamping members that are integral therewith, which engage round longitudinal
30 sides of the strips 4 that face away from each other, as a result of which the connecting device 7 is firmly attached to the unit consisting of wiper blade 2 and strips 4. The oscillating wiper arm 8 is pivotally connected to the

connecting device 7 about a pivot axis near one end, and that in the following manner.

With reference to figure 2 the connecting device 7 comprises
5 two cylindrical protrusions 10 extending outwards on either side of said connecting device 7 (figure 2a). These protrusions 10 pivotally engage in identically shaped cylindrical recesses 11 of a plastic joint part 12 (figure 2b). Said protrusions 10 act as bearing surfaces at the
10 location of a pivot axis in order to pivot the joint part 12 (and the oscillating wiper arm 8 attached thereto) about said pivot axis near one end of said arm 8. The protrusions 10 are preferably in one piece with the connecting device 7; in the alternative, the protrusions 10 are part of a single pivot
15 pin perpendicular to the connecting device 7. Said connecting device 7 may be equipped with a cover or cap in order to obtain an aesthetic appearance thereof, to avoid sharp edges and to provide protection against UV-light etcetera. The joint part 12 comprises two lateral resilient tongues 13
20 extending outwardly, while the oscillating arm 8 has a U-shaped cross-section at the location of its connection to said joint part 12, so that each tongue 13 engages in an identically shaped hole 14 provided in a leg 15 of said U-shaped cross-section (figure 2c).

25

Figures 3a, 3b and 3c correspond to figures 2a, 2b and 2c, respectively, with the difference that one resilient tongue 13 in figure 3 fits in a hole 14 provided in a base 16 of the U-shaped cross-section (figure 3c).

30

Referring to both figures 2 and 3, while mounting the oscillating wiper arm 8 onto the connecting device 7/joint part 12, the resilient tongue(s) 13 is/are initially pushed

in against a spring force and then allowed to spring back into said hole(s) 14, thus snapping, that is clipping the resilient tongue(s) 13 into the hole(s) 14. This is a so-called bayonet-connection.

5

Each leg 15 of the U-shaped cross-section comprises clamping members which engage round longitudinal sides of said joint part 12 that face away from each other. In figures 2, 3 and 4 these clamping members are formed as inwardly bended edges 17
10 integral with the legs 15 of the U-shaped cross-section, serving to further enhance the retention of the oscillating arm 8 onto the connecting device 7/joint part 12 in vertical direction, that is perpendicular to the longitudinal direction of the oscillating wiper arm 8.

15

With reference to figure 5 each leg 15 of the U-shaped cross-section is provided with a first stop surface 19 formed by a downwardly extending protrusion in the form of a hook 20, as can be seen in figure 5b. The legs of the U-shaped cross-
20 section of the joint part 12 each comprise a laterally extending edge 21 equipped with an upwardly extending protrusion in the form of a hook 22, wherein said hook 22 forms a second stop surface 23 provided on the joint part 12 (see figure 5a).

25

In assembled position (figure 6a) both stop surfaces 19,23 are located at a distance from each other. However, in case the first retaining means would disfunction, for example when the resilient tongue 13 would not properly fit into the hole
30 14, the connecting device 7 and the joint part 12 attached thereto would be able to move relative to the oscillating arm 8 in longitudinal direction of the wiper blade 2, that is in the direction of the arrow 24 (figure 6b). Simultaneously,

the second stop surface 23 will move in the same direction until it is stopped by the first stop surface 19. Both stop surfaces 19,23 will then be adjacent to each other (figure 6b). In other words, the mutually cooperating stop surfaces 19,23 function as second retaining means for retaining the connecting device 7 onto the oscillating arm 8.

Figure 7a and 7b refer to another embodiment of the second retaining means. In this case the first stop surface 19 is formed by an inwardly extending transverse pin 26, whereas the second stop surface 23 is formed by a correspondingly shaped guiding groove 27 in the connecting device 7. The guiding groove 27 serves to guide the pin 26 in mounted position onto the connecting device 7. Again, in case the first retaining means would fail, the connecting device 7 and the joint part 12 attached thereto would be able to move relative to the oscillating arm 8 in longitudinal direction of the wiper blade 2. Again, the second stop surface 23 will move in the same direction until it is stopped by the first stop surface 19 formed by the inwardly extending pin 26. Both stop surfaces 19,23 will then be adjacent to each other. The mutually cooperating stop surfaces 19 (formed by the inwardly extending transverse pin 26), 23 (formed by the groove 27 in the connecting device 7) function as second retaining means for retaining the connecting device 7 onto the oscillating arm 8.

Figure 8 shows the steps of mounting or dismounting the connecting device onto or from the oscillating arm 8. While carrying out a pivoting movement of the connecting device 7 and the joint part 8 attached thereto relative to the oscillating arm 8 (or vice versa) the stop surfaces 19,23 are no longer in line and cannot mutually cooperate any longer,

12

so that the connecting device 7 and the joint part 12 attached thereto can be released from the oscillating arm 8 (figures 8a and 8b). Figure 8c refers to the normal "locked" position.

5

Possibly, a spoiler 18 is furthermore provided (figure 1).

The invention is not restricted to the variants shown in the drawing, but it also extends to other embodiments that fall
10 within the scope of the appended claims.